



CAUTION
This product requires a
PXI/cPCI Chassis with
replaceable card guides
per the Eurocard mech-
anical specification

PX413S
Dual 8 x 1
Multiplexer
Module

The PX413S provides 16 independent latching DPST switches configured as dual 8 x 1 multiplexers or a single 16 x 1 multiplexer. These two wire switches have maskable interrupts that occur when the requested relay movements have been made. The module also has a FIFO for storing up to eight relay operations. This module is useful when instrument multiplex switching is needed in your system.

This unit also features a position for adding one single-wide M-Module.

Specifications:

Inputs:

Maximum Voltage (terminal to terminal or chassis) \*\*

DC: 60V / 200V
AC rms: 48V / 125V
AC peak: 68V / 175V

Maximum Current (non-inductive) Per Switch/Per Module:

DC: 2A / 8A
AC peak: 2A/8A

Maximum Power Per Switch/Per Module:

DC: 50W / 200W
AC: 50VA / 200VA

DC Characteristics\*\*:

Thermal Offset: <3\_V (typical)
Contact Resistance: <0.2\_
Insulation Resistance: 10E8 \_

\*\* See manual for conditions

AC Characteristics:

Bandwidth (-3dB): >10 MHz (typ)
Crosstalk (typical)
<100 KHz: <-64 dB
<1 MHz <-44 dB
<10 MHz <-24 dB

Closed channel capacitance:

Ch-Ch: <20 pF \*\*
Hi-Lo: <40 pF \*\*
Ch-chassis: <75 pF \*\*

Typical Relay Life at Rated Load:

10E5 operations

Time to close or open:

8 ms
(female)

Connectors:

Temperature:
Operating: 0°C to 55°C
Storage: -40°C to 75°C

Power: +5V @ 0.6 A

CPCI/PXI Compliance

Complies with PCI spec. 2.0 R3.0 and PCI spec 2.2

5V and 3.3V signaling voltage (VIO) supported

5V only power supply

33MHz PCI data bus

Five trigger lines compliant with PXI Specification 2.1

Form Factor: Size 3U

Applications

- LF Signal Multiplexing
• Multiplexer front or back end for the PX412S Matrix

Ordering Information

Part Number 11030200-0001

Additional Information

User Manuals can be found on our website at www.chtech.com.